

800



PERFORMANCE

TYPE		D350 MEDIUM STILE DOOR
Size (Width X Height)		3'-0" x 7'-0"
ASTM E 283-91	Air Infiltration @ 6.24	<2.00 cfm/ft ²
ASTM E 331-96	Water Test Pressure	1.57 psf
ASTM E 330-97	Uniform Structural Test ± Pressure	82.50 psf
AAMA 507	Thermal Simulation (Glass U-Factor 0.30)	0.73

D SERIES COMMERCIAL DOORS

Features & Options:

Butt Hinge / Offset Pivot
 Center Hung / Offset Hung with C.O.C / Floor Closer
 Standard / C-Pull and Push Handles
 Long /Short Lever Handle
 Paddle Release / Panic Device
 Standard Ms Lock / Latch Lock
 Electric Strike / Magnetic Lock

- Clear Anodized
- Dark Bronze Anodized
- White Painted
- Custom Finishes Available

Other Options: specific hardware upon request

D-SERIES DOORS WITH FG-SERIES FLUSH GLAZE SYSTEM

Model	Size (Width X Height)	Break Type
FG-450	(1-3/4" x 4-1/2")	Non-Thermal Break
FG-451	(2" x 4-1/2")	Non-Thermal Break
FG-451 T	(2" x 4-1/2")	Thermal Break



CUSTOM SHAPED ENTRANCE

Location: PATTERSON, NJ

CUSTOM SHAPED ENTRANCE

Location: 4515 12Ave., Brooklyn, NY

