

# SK2000 ARCHITECTURAL SKYLIGHT



**G**AMCO custom manufactures structural glass skylights and solariums for commercial applications.

The SK-2000 Series skylight systems utilize extruded aluminum members with integral condensate gutter gasket pockets to channel any moisture to the exterior of the structures, thus preventing air and moisture infiltration. This offers a clean appearance, while structurally meeting the required design loads and deflection criteria. Units are available in curb mount self-flashing styles to the exact designs needed for your projects.

- Clear Anodized
- Dark Bronze Anodized
- White Painted
- Custom Finishes Available



**COMMERCIAL BUILDING**  
Profile: Double Pitch Ridge with Gable End  
Location: Brooklyn, NY

**COMMERCIAL BUILDING**  
Profile: Double Pitch Hipped Ridge  
Location: Long Island City, NY

## PERFORMANCE

TYPE		SINGLE PITCH	PYRAMID	DOUBLE PITCH GABLE END
Size (Width X Height)		10'-0" (W) X 10'-0" (L)	10'-0" (W) X 10'-0" (L) X 3'-7" (H)	5'-0" (W) X 10'-0" (L) X 2'-2" (H)
ASTM E 283-99	Static Pressure Air Infiltration @ 6.24 psf	<0.01 cfm/ft <sup>2</sup>	<0.01 cfm/ft <sup>2</sup>	<0.03 cfm/ft <sup>2</sup>
ASTM E 331-00	Static Pressure Water Resistance	15 psf	15 psf	18 psf
ASTM E 330-96	Uniform Structural Design Load ± Pressure	90 psf	90 psf	120 psf
	Uniform Structural Over Load ± Pressure	120 psf	120 psf	180 psf